

The information provided herein is from CONNPLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNPLY or its affiliates. Unauthorized use or modification is strictly prohibited without prior written consent from CONNPLY. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any format or manner. CONNPLY may enforce its intellectual property rights at its own discretion, failures or delays to exercise such rights does not constitute a waiver of such rights.

Dept	Qty
DC	1
ED	1
IE	1
ISO	1
PD	1
R&D	1
SD	1
QA	1
QC	1
QE	1

(110)

22 22 22

85

1M4F

(110)

22 22 22

85

1F4M

(Series Image-Reference Only)

Notes:

Specifications:

- Contact Resistance: 0.5mΩ Max.
- Insulation Resistance: 1000MQ Min.
- Current Rating:50A.
- Voltage Rating:1500V DC.
- Degree of protection: IP2X/IP67
- Temperature: -40°C~+90°C.

Materials:

- Insulating material: Thermoplastic,Black, UL 94 V-0 or UL 94 HB.
- Waterproof Plug: Silicone rubber,Salmon.
- Contact material: Copper alloy,Tin plated.

Product Number Code:

DS1186-03 - X X X X X

- Packing Type
P: Polybag
- Contact plating
6: Tin
- Housing color
B: Black
- Connector type
A: Adaptor
- No. of contacts
1F4M: 1Female+4Male
1M4F: 1Male+4Female
1T4: 1F4M+1M4F

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION	TITLE
X.	±0.60	X.	±5°	mm	Solar Branch Connector 1 To 4 Type
.X	±0.38	.X	±3°	A4	SERIES DS1186-03 SERIES
.XX	±0.25	.XX	±2°		
DRAWING TYPE		CUSTOMER			
SCALE		1:1	SHEET 1 OF 1		
DRAWING NO.		C-DS1186-03-XXXXX-A			

晨翔电子有限公司
CONNFLY CONNPLY ELECTRONIC CO. LTD