

1

2

3

4

5

6

7

8

Dept

Qty

DC

1

ED

1

IE

1

ISO

1

PD

1

R&D

1

SD

1

QA

1

QC

1

QE

1

1

2

3

4

5

6

7

8

REV.

DESCRIPTION

DRAWN

CHECKED

APPROVED

A

NEW RELEASE

JLZ 05/30/23'

1

2

3

4

5

6

7

8

Notes:

Specifications:

1. Contact Resistance: 0.5mΩ Max.

2. Insulation Resistance: 1000MΩ Min.

3. Current Rating:50A.

4. Voltage Rating:1500V DC.

5. Degree of protection: IP2X/IP67

6. Temperature: -40°C~+90°C.

Materials:

1. Insulating material: Thermoplastic,Black.

2. Waterproof Plug: Silicone rubber,Salmon.

3. Contact material: Copper alloy,Tin plated.

Product Number Code:

DS1186-04 - X X X X X

Packing Type

P: Polybag

Contact plating

6: Tin

Housing color

B: Black

Connector type

A: Adaptor

No. of contacts

1F5M: 1Female+5Male

1M5F: 1Male+5Female

1T5: 1F5M+1M5F

1

2

3

4

5

6

7

8

1M5F

1F5M

1

2

3

4

5

6

7

8

GENERAL TOLERANCE

ANGLE TOLERANCE

PROJECTION

TITLE

Solar Branch Connector 1 To 5 Type

UNITS

mm

SHEET SIZE

A4

SERIES

DS1186-04 SERIES

DRAWING TYPE

CUSTOMER

SCALE

1:1

SHEET

1 OF 1

DRAWING NO.

C-DS1186-04-XXXXX-A

1

2

3

4

5

6

7

8

晨翔电子有限公司

CONNELY CONNELY ELECTRONIC CO. LTD