



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 09/04/17'	~	

NOTES:

- MAIN SPECIFICATIONS
 - Housing material: NYLON 66
 - Rated voltage: 250V
 - Rated current: 5A
 - Contact resistance: $\leq 100m\Omega$
 - Insulation resistance: $\geq 1000M\Omega$
 - Withstanding voltage: 500V, AC 1 minute
 - Temperature range: $-25^{\circ}C \sim +85^{\circ}C$
 - Recommend PC board thickness: 1.6mm

2. PRODUCT NUMBER CODE:

DS1073-06- X X X X X

- Contact Plating
6: Tin
8: Full gold flash
- Housing Color
T: Transparent
- Mounting type
V: V/T type
- Connector type
M: Male
- No. of contact
2*2-2*12

RECOMMEND PCB LAYOUT
(TOLERANCE=±0.05)

N=No. of contact/2

Tel: 86-574-63508787
 Fax: 86-574-63510817
 E-mail: sale@connfly.com
 http://www.connfly.com
 Add: East Industry Zone KuangYan
 Town Cixi Ningbo China
 P.C: 315333

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE
X.	±0.60	X.	±5°	UNITS	mm	4.20mm ATX Connector V/T Square Pin Type
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES DS1073-06 SERIES
.XX	±0.25	.XX	±2°			
DRAWING TYPE		CUSTOMRE		晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD		
SCALE		1:1	SHEET 1 OF 1			
DRAWING NO.		C-DS1073-06-XXXXX-A				